


 **RUCOINX[®]**

A SAKATA INX COMPANY

Printing inks for **glass**



1857
166 YEARS
2023



Contents



- **937LED** for hollow glassware and flat glass surfaces as well as ceramics
- **T28** for glass and ceramics
- **110GE** for glass and ceramics

Page 4

Page 6

Page 7



Screen printing inks, LED curing, UV curing

937LED



Your benefits

- Free from phthalates and cyclohexanone as well as aromatic solvents, barium and bromine
- **New development with future-oriented raw materials**
- Corresponds to common industrial standards and the
 - EuPIA Exclusion Policy
 - REACH regulation (SVHC)
 - GADSL list
- Compliant with the current European standard EN 71-3 (exclusively for basic colour shades, white and black)
- RoHS compliant (2015/863/EU) // (2011/65/EU)
- Suitable for curing both with LED technology and conventional UV systems (Hg-, Fe-doped)
- Thermal post-treatment is not required
- Significant time, energy and space savings
- Excellent adhesion and scratch resistance immediately after LED or UV curing, high process reliability is therefore guaranteed
- Good resistance against chemicals (alkalines, solvents), water and abrasion
- Production speed of up to 110 cycles / min.
- Environmentally-friendly alternative to ceramic inks
- High dishwasher resistance (500 / 2,000 cycles minimum in household / industrial dishwasher)
- Ice water and frost resistance up to -20°C
- High light fastness and weather resistance

Characteristics

- 2C screen printing ink, LED curing, UV curing
- High opacity, high gloss and high reactivity

Product range

- 11 basic colour shades and transparent white
- Process colours for 4-colour set
- Highly opaque white and black
- Products for special effects



The all-rounder for
printing onto glass



T28



Your benefits

- Free from phthalates and cyclohexanone as well as aromatic solvents, barium, fluorine and bromine
- Corresponds to common industrial standards and the
 - EuPIA Exclusion Policy
 - REACH regulation (SVHC)
 - GADSL list
- Compliant with the current European standard EN 71-3 (exclusively for basic colour shades, white and black)
- RoHS compliant (2015/863/EU) // (2011/65/EU)
- Universal pad printing ink for printing and coating of glass and ceramics
- Drying of ink film at room temperature or heat-forced oven drying at 80°C within 20 minutes
- Excellent adhesion immediately after heat-drying
- Excellent resistance against chemicals (alkalines, solvents), water and abrasion
- High dishwasher resistance (500 / 2,000 cycles minimum in household / industrial dishwasher)
- Ice water and frost resistance up to -20°C
- High light fastness and weather resistance

Characteristics

- 2C pad printing ink
- Highly opaque, glossy and physically drying

Product range

- 11 basic colour shades and transparent white
- Process colours for 4-colour set
- Highly opaque white and black
- Silver and gold



Screen printing inks
Pad printing inks

110GE



■ Your benefits

- Free from phthalates, fluorine and bromine
- Corresponds to common industrial standards and the
 - EuPIA Exclusion Policy
 - REACH regulation (SVHC)
 - GADSL list
- Compliant with the current European standard EN 71-3 (exclusively for basic colour shades, white and black)
- RoHS compliant (2015/863/EU) // (2011/65/EU)
- Oven-drying of ink film at 180°C within 20 minutes
- Very good adhesion immediately after heat-drying
- Excellent resistance against chemicals (alkalines, solvents), water and abrasion
- High dishwasher resistance (500 / 2,000 cycles minimum in household / industrial dishwasher)
- Ice water and frost resistance up to -20°C
- High light fastness and weather resistance

■ Characteristics

- 1C screen printing ink, 1C pad printing ink
- Highly opaque, glossy and physically drying

■ Product range

- 11 basic colour shades and transparent white
- Process colours for 4-colour set
- Highly opaque white and black
- Fluorescent and transparent inks for special effects, metallic, glitter, matt and frost effects



RUCOINX Printing Inks, A. M. Ramp & Co. GmbH

Lorsbacher Straße 28 • 65817 Eppstein/Ts.

Phone: +49 61 98 30 40 • Fax: +49 61 98 3 22 88

info.de@inx europe.com • www.ruco-inks.com • www.inxeurope.com